


O-Ring



ID	C/S		NO.
	O-Ring	Washer	
0.50	0.50	0.46	EKM
0.50	1.00	0.93	EKM
0.60	0.50	0.46	EKM
0.70	0.50	0.46	EKM
0.74	1.02	0.95	A-001
0.80	0.50	0.46	EKM
0.80	1.00	0.93	EKM
1.00	0.50	0.46	EKM
1.00	1.00	0.93	EKM
1.00	2.00	1.90	EKM
1.07	1.27	1.20	A-002
1.24	2.62	2.50	A-102
1.42	1.53	1.45	A-003
1.50	0.50	0.46	EKM
1.50	1.00	0.93	EKM
1.50	1.50	1.42	EKM
1.50	2.00	1.90	EKM
1.78	1.78	1.68	A-004
1.80	1.80	1.70	C92
2.00	0.50	0.46	EKM
2.00	1.00	0.93	EKM
2.00	1.50	1.42	EKM
2.00	1.80	1.70	C92
2.00	2.00	1.90	EKM
2.06	2.62	2.50	A-103
2.24	1.80	1.70	C92
2.40	1.90	1.80	R-0
2.50	0.50	0.46	EKM
2.50	1.00	0.93	EKM
2.50	1.50	1.42	EKM
2.50	1.50	1.42	S3
2.50	1.80	1.70	C92
2.57	1.78	1.68	A-005
2.60	1.90	1.80	R-1
2.80	1.80	1.70	C92
2.80	1.90	1.80	P3
2.84	2.62	2.50	A-104
2.90	1.78	1.68	A-006
2.90	1.78	1.68	B-1
3.00	0.50	0.46	EKM

ID	C/S		NO.
	O-Ring	Washer	
3.00	1.00	0.93	EKM
3.00	1.50	1.42	EKM
3.00	2.00	1.90	EKM
3.00	3.00	2.87	EKM
3.15	1.80	1.70	C92
3.40	1.90	1.80	R-2
3.50	1.00	0.93	EKM
3.50	1.50	1.42	EKM
3.50	1.50	1.42	S4
3.50	2.00	1.90	EKM
3.55	1.80	1.70	C92
3.63	2.62	2.50	A-105
3.68	1.78	1.68	A-007
3.68	1.78	1.68	B-2
3.75	1.80	1.70	C92
3.80	1.90	1.80	P4
4.00	0.50	0.46	EKM
4.00	1.00	0.93	EKM
4.00	1.50	1.42	EKM
4.00	1.80	1.70	C92
4.00	2.00	1.90	EKM
4.00	2.50	2.39	EKM
4.00	3.00	2.87	EKM
4.00	4.00	3.85	EKM
4.20	1.90	1.80	R-3
4.34	3.53	3.39	A-201
4.42	2.62	2.50	A-106
4.47	1.78	1.68	A-008
4.47	1.78	1.68	B-3
4.50	1.00	0.93	EKM
4.50	1.50	1.42	EKM
4.50	1.50	1.42	S5
4.50	1.80	1.70	C92
4.50	2.00	1.90	EKM
4.70	1.42	1.34	A-901
4.80	1.90	1.80	P5
4.87	1.80	1.70	C92
4.90	1.90	1.80	R-4
5.00	0.50	0.46	EKM
5.00	1.00	0.93	EKM

ID	C/S		NO.
	O-Ring	Washer	
5.00	1.50	1.42	EKM
5.00	1.80	1.70	C92
5.00	2.00	1.90	EKM
5.00	2.50	2.39	EKM
5.00	3.00	2.87	EKM
5.00	5.00	4.84	EKM
5.15	1.80	1.70	C92
5.23	2.62	2.50	A-107
5.28	1.78	1.68	A-009
5.28	1.78	1.68	B-4
5.30	1.80	1.70	C92
5.50	1.50	1.42	EKM
5.50	1.50	1.42	S6
5.60	1.80	1.70	C92
5.70	1.90	1.80	R-5
5.80	1.90	1.80	P6
5.94	3.53	3.39	A-202
6.00	1.00	0.93	EKM
6.00	1.50	1.42	EKM
6.00	1.80	1.70	C92
6.00	2.00	1.90	EKM
6.00	2.50	2.39	EKM
6.00	3.00	2.87	EKM
6.00	5.00	4.84	EKM
6.00	6.00	5.78	EKM
6.02	2.62	2.50	A-108
6.07	1.63	1.54	A-902
6.07	1.78	1.68	A-010
6.07	1.78	1.68	B-5
6.30	1.80	1.70	C92
6.40	1.90	1.80	R-05a
6.50	1.00	0.93	EKM
6.50	1.50	1.42	EKM
6.50	1.50	1.42	S7
6.50	2.00	1.90	EKM
6.50	3.00	2.87	EKM
6.70	1.80	1.70	C92
6.80	1.90	1.80	P7
6.90	1.80	1.70	C92
7.00	0.50	0.46	EKM

ID	C/S		NO.
	O-Ring	Washer	
7.00	1.00	0.93	EKM
7.00	1.50	1.42	EKM
7.00	2.00	1.90	EKM
7.00	2.50	2.39	EKM
7.00	3.00	2.87	EKM
7.10	1.80	1.70	C92
7.10	2.65	2.53	C92
7.20	1.90	1.80	R-6
7.50	1.50	1.42	S8
7.50	1.80	1.70	C92
7.50	2.00	1.90	EKM
7.50	2.50	2.39	EKM
7.50	2.65	2.53	C92
7.52	3.53	3.39	A-203
7.60	2.62	2.50	A-109
7.65	1.63	1.54	A-903
7.65	1.78	1.68	A-011
7.65	1.78	1.68	B-6
7.80	1.90	1.80	P8
8.00	0.50	0.46	EKM
8.00	1.00	0.93	EKM
8.00	1.50	1.42	EKM
8.00	1.80	1.70	C92
8.00	1.90	1.80	R-06a
8.00	2.00	1.90	EKM
8.00	2.50	2.39	EKM
8.00	2.65	2.53	C92
8.00	3.00	2.87	EKM
8.00	4.00	3.85	EKM
8.00	5.00	4.84	EKM
8.50	0.50	0.46	EKM
8.50	1.00	0.93	EKM
8.50	1.50	1.42	EKM
8.50	1.50	1.42	S9
8.50	1.80	1.70	C92
8.50	2.00	1.90	EKM
8.50	2.50	2.39	EKM
8.50	2.65	2.53	C92
8.75	1.80	1.70	C92
8.75	2.65	2.53	C92

ID	C/S		NO.
	O-Ring	Washer	
8.80	1.90	1.80	P9
8.90	1.90	1.80	R-7
8.90	2.70	2.58	R-8
8.92	1.83	1.73	A-904
9.00	0.50	0.46	EKM
9.00	1.00	0.93	EKM
9.00	1.50	1.42	EKM
9.00	1.80	1.70	C92
9.00	2.00	1.90	EKM
9.00	2.50	2.39	EKM
9.00	2.65	2.53	C92
9.00	3.00	2.87	EKM
9.00	4.00	3.85	EKM
9.00	4.50	4.34	EKM
9.12	3.53	3.39	A-204
9.19	2.62	2.50	A-110
9.19	2.62	2.50	B-8
9.25	1.78	1.68	A-012
9.25	1.78	1.68	B-7
9.50	1.00	0.93	EKM
9.50	1.50	1.42	S10
9.50	1.80	1.70	C92
9.50	2.00	1.90	EKM
9.50	2.65	2.53	C92
9.80	1.90	1.80	P10
9.80	2.40	2.29	P10A
10.00	1.00	0.93	EKM
10.00	1.50	1.42	EKM
10.00	1.80	1.70	C92
10.00	2.00	1.90	EKM
10.00	2.50	2.39	EKM
10.00	2.65	2.53	C92
10.00	3.00	2.87	EKM
10.00	4.00	3.85	EKM
10.00	5.00	4.84	EKM
10.46	5.33	5.16	A-309
10.50	1.50	1.42	EKM
10.50	2.70	2.58	R-9
10.52	1.83	1.73	A-905
10.60	1.80	1.70	C92


ID	C/S		NO.
	O-Ring	Washer	
10.60	2.65	2.53	C92
10.69	3.53	3.39	A-205
10.70	1.50	1.42	S11.2
10.77	2.62	2.50	A-111
10.77	2.62	2.50	B-9
10.80	2.40	2.29	P11
10.82	1.78	1.68	A-013
11.00	1.00	0.93	EKM
11.00	1.50	1.42	EKM
11.00	2.00	1.90	EKM
11.00	2.40	2.29	P11.2
11.00	2.50	2.39	EKM
11.00	3.00	2.87	EKM
11.00	4.00	3.85	EKM
11.20	1.80	1.70	C92
11.20	2.65	2.53	C92
11.50	1.50	1.42	EKM
11.50	1.50	1.42	S12.5
11.50	2.00	1.90	EKM
11.50	2.50	2.39	EKM
11.50	3.00	2.87	EKM
11.80	1.80	1.70	C92
11.80	2.40	2.29	P12
11.80	2.65	2.53	C92
11.89	1.98	1.88	A-906
12.00	1.00	0.93	EKM
12.00	1.50	1.42	EKM
12.00	1.50	1.42	S13
12.00	2.00	1.90	EKM
12.00	2.50	2.39	EKM
12.00	3.00	2.87	EKM
12.00	3.50	3.37	EKM
12.00	4.00	3.85	EKM
12.00	5.00	4.84	EKM
12.07	5.33	5.16	A-310
12.10	2.70	2.58	R-10
12.29	3.53	3.39	A-206
12.30	2.40	2.29	P12.5
12.37	2.62	2.50	A-112
12.37	2.62	2.50	B-10

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section (C/S) is less than 5mm, inside diameter (I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
12.42	1.78	1.68	A-014
12.50	1.50	1.42	EKM
12.50	1.80	1.70	C92
12.50	2.00	1.90	EKM
12.50	2.50	2.39	EKM
12.50	2.65	2.53	C92
13.00	1.00	0.93	EKM
13.00	1.50	1.42	EKM
13.00	2.00	1.90	EKM
13.00	2.50	2.39	EKM
13.00	3.00	2.87	EKM
13.20	1.80	1.70	C92
13.20	2.65	2.53	C92
13.47	2.08	1.97	A-907
13.50	1.50	1.42	S14
13.60	2.70	2.58	R-11
13.64	5.33	5.16	A-311
13.80	2.40	2.29	P14
13.87	3.53	3.39	A-207
13.94	2.62	2.50	A-113
13.94	2.62	2.50	B-11
14.00	1.00	0.93	EKM
14.00	1.50	1.42	EKM
14.00	1.78	1.68	A-015
14.00	1.80	1.70	C92
14.00	2.00	1.90	EKM
14.00	2.50	2.39	EKM
14.00	2.65	2.53	C92
14.00	3.00	2.87	EKM
14.00	4.00	3.85	EKM
14.50	0.40	0.37	EKM
14.50	0.50	0.46	EKM
14.50	0.60	0.55	EKM
14.50	0.70	0.65	EKM
14.50	0.80	0.74	EKM
14.50	1.50	1.42	S15
14.50	4.00	3.85	V15
14.80	2.40	2.29	P15
15.00	0.40	0.37	EKM
15.00	0.50	0.46	EKM

ID	C/S		NO.
	O-Ring	Washer	
15.00	0.60	0.55	EKM
15.00	0.70	0.65	EKM
15.00	0.80	0.74	EKM
15.00	1.00	0.93	EKM
15.00	1.50	1.42	EKM
15.00	1.80	1.70	C92
15.00	2.00	1.90	EKM
15.00	2.50	2.39	EKM
15.00	2.65	2.53	C92
15.00	3.00	2.87	EKM
15.00	3.50	3.37	EKM
15.00	4.00	3.85	EKM
15.00	5.00	4.84	EKM
15.10	2.70	2.58	R-12
15.24	5.33	5.16	A-312
15.47	3.53	3.39	A-208
15.50	0.40	0.37	EKM
15.50	0.50	0.46	EKM
15.50	0.60	0.55	EKM
15.50	0.70	0.65	EKM
15.50	0.80	0.74	EKM
15.50	1.50	1.42	S16
15.54	2.62	2.50	A-114
15.54	2.62	2.50	B-12
15.60	1.78	1.68	A-016
15.80	2.40	2.29	P16
16.00	0.40	0.37	EKM
16.00	0.50	0.46	EKM
16.00	0.60	0.55	EKM
16.00	0.70	0.65	EKM
16.00	0.80	0.74	EKM
16.00	0.80	0.74	EKM
16.00	1.00	0.93	EKM
16.00	1.50	1.42	EKM
16.00	1.80	1.70	C92
16.00	2.00	1.90	EKM
16.00	2.50	2.39	EKM
16.00	2.65	2.53	C92
16.00	3.00	2.87	EKM
16.00	4.00	3.85	EKM
16.00	4.50	4.34	EKM

ID	C/S		NO.
	O-Ring	Washer	
16.00	5.00	4.84	EKM
16.36	2.21	2.10	A-908
16.50	0.40	0.37	EKM
16.50	0.50	0.46	EKM
16.50	0.60	0.55	EKM
16.50	0.70	0.65	EKM
16.50	0.80	0.74	EKM
16.81	5.33	5.16	A-313
16.90	2.70	2.58	R-13
17.00	0.40	0.37	EKM
17.00	0.50	0.46	EKM
17.00	0.60	0.55	EKM
17.00	0.70	0.65	EKM
17.00	0.80	0.74	EKM
17.00	1.00	0.93	EKM
17.00	1.50	1.42	EKM
17.00	1.80	1.70	C92
17.00	2.00	1.90	EKM
17.00	2.50	2.39	EKM
17.00	2.65	2.53	C92
17.00	4.00	3.85	EKM
17.04	3.53	3.39	A-209
17.12	2.62	2.50	A-115
17.12	2.62	2.50	B-13
17.17	1.78	1.68	A-017
17.50	0.40	0.37	EKM
17.50	0.50	0.46	EKM
17.50	0.60	0.55	EKM
17.50	0.70	0.65	EKM
17.50	0.80	0.74	EKM
17.50	1.50	1.42	S18
17.50	2.00	1.90	EKM
17.80	2.40	2.29	P18
17.94	2.46	2.35	A-909
18.00	0.40	0.37	EKM
18.00	0.50	0.46	EKM
18.00	0.60	0.55	EKM
18.00	0.70	0.65	EKM
18.00	0.80	0.74	EKM
18.00	1.00	0.93	EKM

ID	C/S		NO.
	O-Ring	Washer	
18.00	1.50	1.42	EKM
18.00	1.80	1.70	C92
18.00	2.00	1.90	EKM
18.00	2.50	2.39	EKM
18.00	2.65	2.53	C92
18.00	3.00	2.87	EKM
18.00	3.50	3.37	EKM
18.00	3.55	3.41	C92
18.00	5.00	4.84	EKM
18.00	6.00	5.78	EKM
18.30	3.60	3.46	R-15
18.40	2.70	2.58	R-14
18.42	5.33	5.16	A-314
18.50	0.40	0.37	EKM
18.50	0.50	0.46	EKM
18.50	0.60	0.55	EKM
18.50	0.70	0.65	EKM
18.50	0.80	0.74	EKM
18.64	3.53	3.39	A-210
18.64	3.53	3.39	B-15
18.72	2.62	2.50	A-116
18.72	2.62	2.50	B-14
18.77	1.78	1.68	A-018
19.00	0.40	0.37	EKM
19.00	0.50	0.46	EKM
19.00	0.60	0.55	EKM
19.00	0.70	0.65	EKM
19.00	0.80	0.74	EKM
19.00	1.00	0.93	EKM
19.00	1.50	1.42	EKM
19.00	1.80	1.70	C92
19.00	2.00	1.90	EKM
19.00	2.50	2.39	EKM
19.00	2.65	2.53	C92
19.00	3.00	2.87	EKM
19.00	3.55	3.41	C92
19.00	4.00	3.85	EKM
19.18	2.46	2.35	A-910
19.40	3.10	2.97	G20
19.50	0.40	0.37	EKM

ID	C/S		NO.
	O-Ring	Washer	
19.50	0.50	0.46	EKM
19.50	0.60	0.55	EKM
19.50	0.70	0.65	EKM
19.50	0.80	0.74	EKM
19.50	1.50	1.42	S20
19.80	2.40	2.29	P20
19.80	3.60	3.46	R-16
19.99	5.33	5.16	A-315
20.00	0.40	0.37	EKM
20.00	0.50	0.46	EKM
20.00	0.60	0.55	EKM
20.00	0.70	0.65	EKM
20.00	0.80	0.74	EKM
20.00	1.00	0.93	EKM
20.00	1.50	1.42	EKM
20.00	1.80	1.70	C92
20.00	2.00	1.90	EKM
20.00	2.50	2.39	EKM
20.00	2.65	2.53	C92
20.00	3.00	2.87	EKM
20.00	3.55	3.41	C92
20.00	4.00	3.85	EKM
20.00	4.50	4.34	EKM
20.00	6.00	5.78	EKM
20.22	3.53	3.39	A-211
20.22	3.53	3.39	B-16
20.29	2.62	2.50	A-117
20.35	1.78	1.68	A-019
20.50	0.40	0.37	EKM
20.50	0.50	0.46	EKM
20.50	0.60	0.55	EKM
20.50	0.70	0.65	EKM
20.50	0.80	0.74	EKM
20.80	2.40	2.29	P21
21.00	0.40	0.37	EKM
21.00	0.50	0.46	EKM
21.00	0.60	0.55	EKM
21.00	0.70	0.65	EKM
21.00	0.80	0.74	EKM
21.00	1.00	0.93	EKM
21.00	1.50	1.42	EKM
21.00	2.00	1.90	EKM
21.00	2.50	2.39	EKM
21.00	3.00	2.87	EKM
21.00	4.00	3.85	EKM
21.00	5.00	4.84	EKM
21.10	3.50	3.37	P22.4
21.40	1.80	1.70	C92

A= AS568, B= BS1516, C=C92
V.S.P.G =JIS EKM=EKStandard, R = France


ID	C/S		NO.
	O-Ring	Washer	
21.00	1.50	1.42	EKM
21.00	2.00	1.90	EKM
21.00	2.50	2.39	EKM
21.00	3.00	2.87	EKM
21.00	3.50	3.37	EKM
21.00	4.00	3.85	EKM
21.20	1.80	1.70	C92
21.20	2.65	2.53	C92
21.20	3.55	3.41	C92
21.30	3.60	3.46	R-17
21.50	0.40	0.37	EKM
21.50	0.50	0.46	EKM
21.50	0.60	0.55	EKM
21.50	0.70	0.65	EKM
21.50	0.80	0.74	EKM
21.50	1.50	1.42	S22
21.59	5.33	5.16	A-316
21.70	3.50	3.37	P22A
21.80	2.40	2.29	P22
21.80	3.10	2.97	G22
21.82	3.53	3.39	A-212
21.82	3.53	3.39	B-17
21.89	2.62	2.50	A-118
21.90	2.00	1.90	S22.4
21.92	2.95	2.82	A-911
21.95	1.78	1.68	A-020
22.00	0.40	0.37	EKM
22.00	0.50	0.46	EKM
22.00	0.60	0.55	EKM
22.00	0.70	0.65	EKM
22.00	0.80	0.74	EKM
22.00	1.00	0.93	EKM
22.00	1.50	1.42	EKM
22.00	2.00	1.90	EKM
22.00	2.50	2.39	EKM
22.00	3.00	2.87	EKM
22.00	4.00	3.85	EKM
22.00	5.00	4.84	EKM
22.10	3.50	3.37	P22.4
22.40	1.80	1.70	C92

●X-Ring: ID≥2.90mm,C/S≥1.78mm is available

●If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
22.40	2.65	2.53	C92
22.40	3.55	3.41	C92
22.50	0.40	0.37	EKM
22.50	0.50	0.46	EKM
22.50	0.60	0.55	EKM
22.50	0.70	0.65	EKM
22.50	0.80	0.74	EKM
23.00	0.40	0.37	EKM
23.00	0.50	0.46	EKM
23.00	0.60	0.55	EKM
23.00	0.70	0.65	EKM
23.00	0.80	0.74	EKM
23.00	1.00	0.93	EKM
23.00	1.50	1.42	EKM
23.00	2.00	1.90	EKM
23.00	2.50	2.39	EKM
23.00	3.00	2.87	EKM
23.00	3.60	3.46	R-18
23.00	4.00	3.85	EKM
23.00	5.00	4.84	EKM
23.16	5.33	5.16	A-317
23.39	3.53	3.39	A-213
23.39	3.53	3.39	B-18
23.47	2.62	2.50	A-119
23.47	2.95	2.82	A-912
23.50	0.40	0.37	EKM
23.50	0.50	0.46	EKM
23.50	0.60	0.55	EKM
23.50	0.70	0.65	EKM
23.50	0.80	0.74	EKM
23.50	2.00	1.90	S24
23.50	4.00	3.85	V24
23.52	1.78	1.68	A-021
23.60	1.80	1.70	C92
23.60	2.65	2.53	C92
23.60	3.55	3.41	C92
23.70	3.50	3.37	P24
24.00	0.40	0.37	EKM
24.00	0.50	0.46	EKM
24.00	0.60	0.55	EKM

ID	C/S		NO.
	O-Ring	Washer	
24.00	0.70	0.65	EKM
24.00	0.80	0.74	EKM
24.00	1.00	0.93	EKM
24.00	1.50	1.42	EKM
24.00	2.00	1.90	EKM
24.00	2.50	2.39	EKM
24.00	3.00	2.87	EKM
24.00	3.50	3.37	EKM
24.00	4.00	3.85	EKM
24.00	5.50	5.33	EKM
24.40	3.10	2.97	G25
24.50	0.40	0.37	EKM
24.50	0.50	0.46	EKM
24.50	0.60	0.55	EKM
24.50	0.70	0.65	EKM
24.50	0.80	0.74	EKM
24.50	2.00	1.90	S25
24.60	3.60	3.46	R-19
24.70	3.50	3.37	P25
24.77	5.33	5.16	A-318
24.99	3.53	3.39	B-19
25.00	0.40	0.37	EKM
25.00	0.50	0.46	EKM
25.00	0.60	0.55	EKM
25.00	0.70	0.65	EKM
25.00	0.80	0.74	EKM
25.00	1.50	1.42	EKM
25.00	1.80	1.70	C92
25.00	2.00	1.90	EKM
25.00	2.50	2.39	EKM
25.00	2.65	2.53	C92
25.00	3.00	2.87	EKM
25.00	3.53	3.39	A-214
25.00	3.55	3.41	C92
25.00	4.00	3.85	EKM
25.00	5.00	4.84	EKM
25.00	6.00	5.78	EKM
25.04	2.95	2.82	A-913
25.07	2.62	2.50	A-120
25.12	1.78	1.68	A-022

ID	C/S		NO.
	O-Ring	Washer	
25.20	3.50	3.37	P25.5
25.50	0.40	0.37	EKM
25.50	0.50	0.46	EKM
25.50	0.60	0.55	EKM
25.50	0.70	0.65	EKM
25.50	0.80	0.74	EKM
25.50	2.00	1.90	S26
25.70	3.50	3.37	P26
25.80	1.80	1.70	C92
25.80	2.65	2.53	C92
25.80	3.55	3.41	C92
26.00	0.40	0.37	EKM
26.00	0.50	0.46	EKM
26.00	0.60	0.55	EKM
26.00	0.70	0.65	EKM
26.00	0.80	0.74	EKM
26.00	1.00	0.93	EKM
26.00	1.50	1.42	EKM
26.00	2.00	1.90	EKM
26.00	2.50	2.39	EKM
26.00	3.00	2.87	EKM
26.00	3.50	3.37	EKM
26.00	4.00	3.85	EKM
26.00	5.00	4.84	EKM
26.00	3.50	3.37	EKM
26.00	4.00	3.85	EKM
26.00	2.50	2.39	EKM
26.00	3.00	2.87	EKM
26.00	3.50	3.37	EKM
26.00	4.00	3.85	EKM
26.00	5.00	4.84	EKM
26.20	3.60	3.46	R-20
26.34	5.33	5.16	A-319
26.50	0.40	0.37	EKM
26.50	0.50	0.46	EKM
26.50	0.60	0.55	EKM
26.50	0.70	0.65	EKM
26.50	0.80	0.74	EKM
26.50	1.80	1.70	C92
26.50	2.65	2.53	C92
26.50	3.55	3.41	C92
26.57	3.53	3.39	A-215
26.57	3.53	3.39	B-20
26.60	2.95	2.82	A-914
26.64	2.62	2.50	A-121
26.70	1.78	1.68	A-023
27.00	0.40	0.37	EKM

ID	C/S		NO.
	O-Ring	Washer	
27.00	0.50	0.46	EKM
27.00	0.60	0.55	EKM
27.00	0.70	0.65	EKM
27.00	0.80	0.74	EKM
27.00	1.50	1.42	EKM
27.00	2.00	1.90	EKM
27.00	2.50	2.39	EKM
27.00	3.00	2.87	EKM
27.00	4.00	3.85	EKM
27.00	5.00	4.84	EKM
27.50	0.40	0.37	EKM
27.50	0.50	0.46	EKM
27.50	0.60	0.55	EKM
27.50	0.70	0.65	EKM
27.50	0.80	0.74	EKM
27.50	2.00	1.90	S28
27.70	3.50	3.37	P28
27.80	3.60	3.46	R-21
27.94	5.33	5.16	A-320
28.00	0.40	0.37	EKM
28.00	0.50	0.46	EKM
28.00	0.60	0.55	EKM
28.00	0.70	0.65	EKM
28.00	0.80	0.74	EKM
28.00	1.00	0.93	EKM
28.00	1.50	1.42	EKM
28.00	1.80	1.70	C92
28.00	2.00	1.90	EKM
28.00	2.50	2.39	EKM
28.00	2.65	2.53	C92
28.00	3.00	2.87	EKM
28.00	3.55	3.41	C92
28.00	4.00	3.85	EKM
28.00	5.00	4.84	EKM
28.17	3.53	3.39	A-216
28.17	3.53	3.39	B-21
28.24	2.62	2.50	A-122
28.30	1.78	1.68	A-024
28.50	0.40	0.37	EKM
28.50	0.50	0.46	EKM

ID	C/S		NO.
	O-Ring	Washer	
28.50	0.60	0.55	EKM
28.50	0.70	0.65	EKM
28.50	0.80	0.74	EKM
28.50	2.00	1.90	S29
28.70	3.50	3.37	P29
29.00	0.40	0.37	EKM
29.00	0.50	0.46	EKM
29.00	0.60	0.55	EKM
29.00	0.70	0.65	EKM
29.00	0.80	0.74	EKM
29.00	2.50	2.39	EKM
29.00	5.00	4.84	EKM
29.20	3.50	3.37	P29.5
29.30	3.60	3.46	R-22
29.40	3.10	2.97	G30
29.50	0.40	0.37	EKM
29.50	0.50	0.46	EKM
29.50	0.60	0.55	EKM
29.50	0.70	0.65	EKM
29.50	0.80	0.74	EKM
29.50	2.00	1.90	S30
29.51	5.33	5.16	A-321
29.70	3.50	3.37	P30
29.74	2.95	2.82	A-916
29.74	3.53	3.39	A-217
29.74	3.53	3.39	B-22
29.82	2.62	2.50	A-123
29.87	1.78	1.68	A-025
30.00	0.40	0.37	EKM
30.00	0.50	0.46	EKM
30.00	0.60	0.55	EKM
30.00	0.70	0.65	EKM
30.00	0.80	0.74	EKM
30.00	1.00	0.93	EKM
30.00	1.50	1.42	EKM
30.00	1.80	1.70	C92
30.00	2.00	1.90	EKM
30.00	2.50	2.39	EKM
30.00	2.65	2.53	C92
30.00	3.00	2.87	EKM


ID	C/S		NO.
	O-Ring	Washer	
30.00	3.55	3.41	C92
30.00	4.00	3.85	EKM
30.00	5.00	4.84	EKM
30.00	6.00	5.78	EKM
30.50	0.40	0.37	EKM
30.50	0.50	0.46	EKM
30.50	0.60	0.55	EKM
30.50	0.70	0.65	EKM
30.50	0.80	0.74	EKM
30.70	3.50	3.37	P31
30.80	3.60	3.46	R-23
31.00	0.40	0.37	EKM
31.00	0.50	0.46	EKM
31.00	0.60	0.55	EKM
31.00	0.70	0.65	EKM
31.00	0.80	0.74	EKM
31.00	2.00	1.90	EKM
31.00	2.50	2.39	EKM
31.00	3.00	2.87	EKM
31.12	5.33	5.16	A-322
31.20	3.50	3.37	P31.5
31.34	3.53	3.39	A-218
31.34	3.53	3.39	B-23
31.42	2.62	2.50	A-124
31.47	1.78	1.68	A-026
31.50	0.40	0.37	EKM
31.50	0.50	0.46	EKM
31.50	0.60	0.55	EKM
31.50	0.70	0.65	EKM
31.50	0.80	0.74	EKM
31.50	1.80	1.70	C92
31.50	2.00	1.90	S32
31.50	2.65	2.53	C92
31.50	3.55	3.41	C92
31.70	3.50	3.37	P32
32.00	0.40	0.37	EKM
32.00	0.50	0.46	EKM
32.00	0.60	0.55	EKM
32.00	0.70	0.65	EKM

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
32.00	0.80	0.74	EKM
32.00	1.50	1.42	EKM
32.00	2.00	1.90	EKM
32.00	2.50	2.39	EKM
32.00	3.00	2.87	EKM
32.00	4.00	3.85	EKM
32.00	5.00	4.84	EKM
32.50	1.80	1.70	C92
32.50	2.65	2.53	C92
32.50	3.55	3.41	C92
32.50	3.60	3.46	R-24
32.69	5.33	5.16	A-323
32.92	3.53	3.39	A-219
32.92	3.53	3.39	B-24
32.99	2.62	2.50	A-125
33.00	1.50	1.42	EKM
33.00	2.00	1.90	EKM
33.00	2.50	2.39	EKM
33.00	3.00	2.87	EKM
33.05	1.78	1.68	A-027
33.50	1.80	1.70	C92
33.50	2.00	1.90	S34
33.50	2.65	2.53	C92
33.50	3.55	3.41	C92
33.50	4.00	3.85	V34
33.70	3.50	3.37	P34
34.00	2.00	1.90	EKM
34.00	4.00	3.85	EKM
34.10	3.60	3.46	R-25
34.29	5.33	5.16	A-324
34.40	3.10	2.97	G35
34.42	2.95	2.82	A-918
34.50	1.80	1.70	C92
34.50	2.00	1.90	S35
34.50	2.65	2.53	C92
34.50	3.55	3.41	C92
34.50	4.00	3.85	V36
34.52	3.53	3.39	A-220
34.52	3.53	3.39	B-25
34.59	2.62	2.50	A-126

ID	C/S		NO.
	O-Ring	Washer	
34.65	1.78	1.68	A-028
34.70	3.50	3.37	P35
35.00	1.50	1.42	EKM
35.00	2.00	1.90	EKM
35.00	2.00	1.90	S35.5
35.00	2.50	2.39	EKM
35.00	3.00	2.87	EKM
35.00	4.00	3.85	EKM
35.00	5.00	4.84	EKM
35.20	3.50	3.37	P35.5
35.50	1.80	1.70	C92
35.50	2.00	1.90	S36
35.50	2.65	2.53	C92
35.50	3.55	3.41	C92
35.60	3.60	3.46	R-26
35.70	3.50	3.37	P36
36.00	1.50	1.42	EKM
36.00	2.00	1.90	EKM
36.00	2.50	2.39	EKM
36.00	3.00	2.87	EKM
36.00	4.00	3.85	EKM
36.00	5.00	4.84	EKM
36.09	3.53	3.39	A-221
36.09	3.53	3.39	B-26
36.17	2.62	2.50	A-127
36.50	1.80	1.70	C92
36.50	2.65	2.53	C92
37.00	2.00	1.90	EKM
37.00	2.50	2.39	EKM
37.00	3.00	2.87	EKM
37.00	4.00	3.85	EKM
37.00	5.33	5.16	B-28
37.30	3.60	3.46	R-27
37.46	3.00	2.87	A-920
37.46	5.33	5.16	B-28
37.47	5.33	5.16	A-325
37.47	5.33	5.16	R-28
37.47	6.99	6.73	A-401
37.50	1.80	1.70	C92
37.50	2.00	1.90	S38

ID	C/S		NO.
	O-Ring	Washer	
37.50	2.65	2.53	C92
37.50	3.55	3.41	C92
37.69	3.53	3.39	A-222
37.69	3.53	3.39	B-27
37.70	3.50	3.37	P38
37.77	2.62	2.50	A-128
37.82	1.78	1.68	A-029
38.00	2.00	1.90	EKM
38.00	2.50	2.39	EKM
38.00	3.00	2.87	EKM
38.00	4.00	3.85	EKM
38.00	4.50	4.34	EKM
38.00	7.00	6.74	EKM
38.50	2.00	1.90	S39
38.70	1.80	1.70	C92
38.70	2.65	2.53	C92
38.70	3.50	3.37	P39
38.70	3.55	3.41	C92
39.00	2.00	1.90	EKM
39.00	2.50	2.39	EKM
39.00	3.00	2.87	EKM
39.34	2.62	2.50	A-129
39.40	3.10	2.97	G40
39.50	2.00	1.90	S40
39.50	4.00	3.85	V40
39.70	3.50	3.37	P40
40.00	1.80	1.70	C92
40.00	2.00	1.90	EKM
40.00	2.50	2.39	EKM
40.00	2.65	2.53	C92
40.00	3.00	2.87	EKM
40.00	3.50	3.37	EKM
40.00	3.55	3.41	C92
40.00	4.00	3.85	EKM
40.00	5.00	4.84	EKM
40.00	5.30	5.13	C92
40.00	5.50	5.33	EKM
40.00	6.00	5.78	EKM
40.64	5.33	5.16	A-326
40.64	5.33	5.16	B-29


ID	C/S		NO.
	O-Ring	Washer	
40.64	5.33	5.16	R-29
40.64	6.99	6.73	A-402
40.70	3.50	3.37	P41
40.87	3.53	3.39	A-223
40.94	2.62	2.50	A-130
41.00	1.78	1.68	A-030
41.00	3.00	2.87	EKM
41.00	4.00	3.85	EKM
41.20	1.80	1.70	C92
41.20	2.65	2.53	C92
41.20	3.55	3.41	C92
41.20	5.30	5.13	C92
41.50	2.00	1.90	S42
41.70	3.50	3.37	P42
42.00	1.00	0.93	EKM
42.00	2.00	1.90	EKM
42.00	2.50	2.39	EKM
42.00	3.00	2.87	EKM
42.00	3.50	3.37	EKM
42.00	4.00	3.85	EKM
42.00	5.00	4.84	EKM
42.50	1.80	1.70	C92
42.50	2.65	2.53	C92
42.50	3.55	3.41	C92
42.50	5.30	5.13	C92
42.52	2.62	2.50	A-131
43.00	2.00	1.90	EKM
43.00	2.50	2.39	EKM
43.00	3.00	2.87	EKM
43.00	3.50	3.37	EKM
43.50	2.00	1.90	S44
43.68	3.00	2.87	A-924
43.70	1.80	1.70	C92
43.70	2.65	2.53	C92
43.70	3.50	3.37	P44
43.70	3.55	3.41	C92
43.70	5.30	5.13	C92
43.82	5.33	5.16	A-327
43.82	5.33	5.16	B-30
43.82	5.33	5.16	R-30

ID	C/S		NO.
	O-Ring	Washer	
43.82	6.99	6.73	A-403
44.00	2.00	1.90	EKM
44.00	2.50	2.39	EKM
44.00	3.00	2.87	EKM
44.00	4.00	3.85	EKM
44.00	5.00	4.84	EKM
44.04	3.53	3.39	A-224
44.12	2.62	2.50	A-132
44.17	1.78	1.68	A-031
44.40	3.10	2.97	G45
44.50	2.00	1.90	S45
44.70	3.50	3.37	P45
45.00	1.50	1.42	EKM
45.00	1.80	1.70	C92
45.00	2.00	1.90	EKM
45.00	2.50	2.39	EKM
45.00	2.65	2.53	C92
45.00	3.00	2.87	EKM
45.00	3.50	3.37	EKM
45.00	3.55	3.41	C92
45.00	4.00	3.85	EKM
45.00	4.50	4.34	EKM
45.00	5.00	4.84	EKM
45.00	5.30	5.13	C92
45.00	5.50	5.33	EKM
45.50	2.00	1.90	S46
45.69	2.62	2.50	A-133
45.70	3.50	3.37	P46
46.00	2.00	1.90	EKM
46.00	2.50	2.39	EKM
46.00	3.00	2.87	EKM
46.00	3.50	3.37	EKM
46.00	4.00	3.85	EKM
46.00	5.00	4.84	EKM
46.20	1.80	1.70	C92
46.20	2.65	2.53	C92
46.20	3.55	3.41	C92
46.20	5.30	5.13	C92
46.99	5.33	5.16	A-328
46.99	5.33	5.16	B-31


ID	C/S		NO.
	O-Ring	Washer	
46.99	6.99	6.73	A-404
47.00	2.50	2.39	EKM
47.00	3.00	2.87	EKM
47.00	4.00	3.85	EKM
47.00	5.00	4.84	EKM
47.00	5.33	5.16	R-31
47.22	3.53	3.39	A-225
47.29	2.62	2.50	A-134
47.35	1.78	1.68	A-032
47.50	1.80	1.70	C92
47.50	2.00	1.90	S48
47.50	2.65	2.53	C92
47.50	3.55	3.41	C92
47.50	5.30	5.13	C92
47.60	5.70	5.53	P48A
47.70	3.50	3.37	P48
48.00	2.00	1.90	EKM
48.00	2.50	2.39	EKM
48.00	3.00	2.87	EKM
48.00	4.00	3.85	EKM
48.00	5.00	4.84	EKM
48.00	6.00	5.78	EKM
48.70	1.80	1.70	C92
48.70	2.65	2.53	C92
48.70	3.50	3.37	P49
48.70	3.55	3.41	C92
48.70	5.30	5.13	C92
48.90	2.62	2.50	A-135
49.00	2.50	2.39	EKM
49.00	3.00	2.87	EKM
49.00	3.50	3.37	EKM
49.40	3.10	2.97	G50
49.50	2.00	1.90	S50
49.50	3.00	2.87	EKM
49.60	5.70	5.53	P50A
49.70	3.50	3.37	P50
ID Over 50mm			
50.00	1.80	1.70	C92
50.00	2.00	1.90	EKM

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section (C/S) is less than 5mm, inside diameter (I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
50.00	2.50	2.39	EKM
50.00	2.65	2.53	C92
50.00	3.00	2.87	EKM
50.00	3.55	3.41	C92
50.00	4.00	3.85	EKM
50.00	4.50	4.34	EKM
50.00	5.00	4.84	EKM
50.00	5.30	5.13	C92
50.00	6.00	5.78	EKM
50.16	5.33	5.16	B-32
50.16	5.33	5.16	R-32
50.16	6.99	6.73	A-405
50.17	5.33	5.16	A-329
50.39	3.53	3.39	A-226
50.47	2.62	2.50	A-136
50.52	1.78	1.68	A-033
51.00	2.50	2.39	EKM
51.00	3.00	2.87	EKM
51.50	2.65	2.53	C92
51.50	3.55	3.41	C92
51.50	5.30	5.13	C92
51.60	5.70	5.53	P52
52.00	1.50	1.42	EKM
52.00	2.00	1.90	EKM
52.00	3.00	2.87	EKM
52.00	3.50	3.37	EKM
52.00	4.00	3.85	EKM
52.00	5.00	4.84	EKM
52.07	2.62	2.50	A-137
52.50	2.00	1.90	S53
52.60	5.70	5.53	P53
53.00	1.50	1.42	EKM
53.00	2.00	1.90	EKM
53.00	2.50	2.39	EKM
53.00	2.65	2.53	C92
53.00	3.00	2.87	EKM
53.00	3.55	3.41	C92
53.00	5.00	4.84	EKM
53.00	5.30	5.13	C92
53.00	6.00	5.78	EKM

ID	C/S		NO.
	O-Ring	Washer	
53.09	3.00	2.87	A-928
53.34	5.33	5.16	A-330
53.34	5.33	5.16	B-33
53.34	5.33	5.16	R-33
53.34	6.99	6.73	A-406
53.57	3.53	3.39	A-227
53.64	2.62	2.50	A-138
53.70	1.78	1.68	A-034
54.00	2.50	2.39	EKM
54.00	3.00	2.87	EKM
54.00	4.00	3.85	EKM
54.00	5.00	4.84	EKM
54.40	3.10	2.97	G55
54.50	2.00	1.90	S55
54.50	2.65	2.53	C92
54.50	3.55	3.41	C92
54.50	4.00	3.85	V55
54.50	5.30	5.13	C92
54.60	5.70	5.53	P55
55.00	2.00	1.90	EKM
55.00	2.50	2.39	EKM
55.00	3.00	2.87	EKM
55.00	3.50	3.37	EKM
55.00	4.00	3.85	EKM
55.00	5.00	4.84	EKM
55.00	6.00	5.78	EKM
55.25	2.62	2.50	A-139
55.50	2.00	1.90	S56
55.60	5.70	5.53	P56
56.00	2.00	1.90	EKM
56.00	2.65	2.53	C92
56.00	3.00	2.87	EKM
56.00	3.55	3.41	C92
56.00	4.00	3.85	EKM
56.00	5.30	5.13	C92
56.52	5.33	5.16	A-331
56.52	5.33	5.16	B-34
56.52	5.33	5.16	R-34
56.52	6.99	6.73	A-407
56.74	3.53	3.39	A-228

ID	C/S		NO.
	O-Ring	Washer	
56.82	2.62	2.50	A-140
56.87	1.78	1.68	A-035
57.00	1.50	1.42	EKM
57.00	2.00	1.90	EKM
57.00	2.50	2.39	EKM
57.00	3.00	2.87	EKM
57.00	4.00	3.85	EKM
57.00	5.00	4.84	EKM
57.60	5.70	5.53	P58
58.00	2.00	1.90	EKM
58.00	2.50	2.39	EKM
58.00	2.65	2.53	C92
58.00	3.00	2.87	EKM
58.00	3.55	3.41	C92
58.00	4.00	3.85	EKM
58.00	5.00	4.84	EKM
58.00	5.30	5.13	C92
58.42	2.62	2.50	A-141
59.00	3.00	2.87	EKM
59.36	3.00	2.87	A-932
59.40	3.10	2.97	G60
59.50	2.00	1.90	S60
59.60	5.70	5.53	P60
59.69	5.33	5.16	A-332
59.69	5.34	5.17	B-35
59.69	5.34	5.17	R-35
59.69	6.99	6.73	A-408
59.92	3.53	3.39	A-229
59.99	2.62	2.50	A-142
60.00	1.50	1.42	EKM
60.00	2.00	1.90	EKM
60.00	2.50	2.39	EKM
60.00	2.65	2.53	C92
60.00	3.00	2.87	EKM
60.00	3.50	3.37	EKM
60.00	3.55	3.41	C92
60.00	4.00	3.85	EKM
60.00	4.50	4.34	EKM
60.00	5.00	4.84	EKM
60.00	5.30	5.13	C92

ID	C/S		NO.
	O-Ring	Washer	
60.00	7.00	6.74	EKM
60.05	1.78	1.68	A-036
61.50	2.65	2.53	C92
61.50	3.55	3.41	C92
61.50	5.30	5.13	C92
61.60	2.62	2.50	A-143
61.60	5.70	5.53	P62
62.00	2.00	1.90	EKM
62.00	2.50	2.39	EKM
62.00	3.00	2.87	EKM
62.00	4.00	3.85	EKM
62.00	5.00	4.84	EKM
62.00	6.00	5.78	EKM
62.50	2.00	1.90	S63
62.60	5.70	5.53	P63
62.87	5.33	5.16	A-333
62.87	5.33	5.16	B-36
62.87	5.33	5.16	R-36
62.87	6.99	6.73	A-409
63.00	2.00	1.90	EKM
63.00	2.50	2.39	EKM
63.00	2.65	2.53	C92
63.00	3.00	2.87	EKM
63.00	3.55	3.41	C92
63.00	5.30	5.13	C92
63.09	3.53	3.39	A-230
63.17	2.62	2.50	A-144
63.22	1.78	1.68	A-037
64.00	3.00	2.87	EKM
64.00	3.50	3.37	EKM
64.00	4.00	3.85	EKM
64.00	5.00	4.84	EKM
64.40	3.10	2.97	G65
64.50	2.00	1.90	S65
64.60	5.70	5.53	P65
64.77	2.62	2.50	A-145
65.00	1.50	1.42	EKM
65.00	1.80	1.70	C92
65.00	2.00	1.90	EKM
65.00	2.50	2.39	EKM

ID	C/S		NO.
	O-Ring	Washer	
65.00	2.65	2.53	C92
65.00	3.00	2.87	EKM
65.00	3.50	3.37	EKM
65.00	3.55	3.41	C92
65.00	4.00	3.85	EKM
65.00	4.50	4.34	EKM
65.00	5.00	4.84	EKM
65.00	5.30	5.13	C92
66.00	2.00	1.90	EKM
66.00	3.00	2.87	EKM
66.04	5.33	5.16	A-334
66.04	5.33	5.16	B-37
66.04	5.33	5.16	R-37
66.04	6.99	6.73	A-410
66.27	3.53	3.39	A-231
66.34	2.62	2.50	A-146
66.40	1.78	1.68	A-038
66.50	2.00	1.90	S67
66.60	5.70	5.53	P67
67.00	1.50	1.42	EKM
67.00	2.00	1.90	EKM
67.00	2.50	2.39	EKM
67.00	2.65	2.53	C92
67.00	3.00	2.87	EKM
67.00	3.55	3.41	C92
67.00	4.00	3.85	EKM
67.00	5.30	5.13	C92
67.95	2.62	2.50	A-147
68.00	2.00	1.90	EKM
68.00	3.00	2.87	EKM
68.00	4.00	3.85	EKM
68.00	5.00	4.84	EKM
68.00	7.00	6.74	EKM
69.00	2.65	2.53	C92
69.00	3.00	2.87	EKM
69.00	3.55	3.41	C92
69.00	4.00	3.85	V70
69.00	5.30	5.13	C92
69.22	5.33	5.16	A-335
69.22	5.33	5.16	B-38

ID	C/S		NO.
	O-Ring	Washer	
69.22	5.33	5.16	R-38
69.22	6.99	6.73	A-411
69.40	3.10	2.97	G70
69.44	3.53	3.39	A-232
69.50	2.00	1.90	S70
69.52	2.62	2.50	A-148
69.57	1.78	1.68	A-039
69.60	5.70	5.53	P70
70.00	2.00	1.90	EKM
70.00	2.50	2.39	EKM
70.00	3.00	2.87	EKM
70.00	4.00	3.85	EKM
70.00	4.50	4.34	EKM
70.00	5.00	4.84	EKM
70.00	8.00	7.60	EKM
70.50	2.00	1.90	S71
70.60	5.70	5.53	P71
71.00	2.65	2.53	C92
71.00	3.00	2.87	EKM
71.00	3.55	3.41	C92
71.00	5.30	5.13	C92
71.12	2.62	2.50	A-149
72.00	1.50	1.42	EKM
72.00	2.00	1.90	EKM
72.00	2.50	2.39	EKM
72.00	3.00	2.87	EKM
72.00	4.00	3.85	EKM
72.00	5.00	4.84	EKM
72.39	5.33	5.16	A-336
72.39	5.33	5.16	B-39
72.39	5.33	5.16	R-39
72.39	6.99	6.73	A-412
72.62	3.53	3.39	A-233
72.69	2.62	2.50	A-150
72.75	1.78	1.68	A-040
73.00	2.50	2.39	EKM
73.00	2.65	2.53	C92
73.00	3.00	2.87	EKM
73.00	3.55	3.41	C92
73.00	5.00	4.84	EKM

50.00


A= AS568、 B= BS1516、 C=C92
V.S.P.G =JIS EKM=EKStandard、 R = France

●X-Ring: ID≥2.90mm,C/S≥1.78mm is available

●If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
73.00	5.30	5.13	C92
74.00	2.00	1.90	EKM
74.00	3.00	2.87	EKM
74.00	4.00	3.85	EKM
74.40	2.65	2.53	C92
74.40	3.10	2.97	G75
74.50	2.00	1.90	S75
74.60	5.70	5.53	P75
75.00	2.50	2.39	EKM
75.00	2.65	2.53	C92
75.00	3.00	2.87	EKM
75.00	3.50	3.37	EKM
75.00	3.55	3.41	C92
75.00	4.00	3.85	EKM
75.00	5.00	4.84	EKM
75.00	5.30	5.13	C92
75.00	6.00	5.78	EKM
75.57	5.33	5.16	A-337
75.57	5.33	5.16	B-40
75.57	5.33	5.16	R-40
75.57	6.99	6.73	A-413
75.79	3.53	3.39	A-234
75.87	2.62	2.50	A-151
75.92	1.78	1.68	A-041
76.00	2.00	1.90	EKM
76.00	2.50	2.39	EKM
76.00	3.00	2.87	EKM
76.00	4.00	3.85	EKM
76.00	4.50	4.34	EKM
77.50	3.55	3.41	C92
77.50	5.30	5.13	C92
78.00	2.00	1.90	EKM
78.00	3.00	2.87	EKM
78.00	4.00	3.85	EKM
78.00	5.00	4.84	EKM
78.74	5.33	5.16	A-338
78.74	5.33	5.16	B-41
78.74	5.33	5.16	R-41
78.74	6.99	6.73	A-414
78.97	3.53	3.39	A-235

ID	C/S		NO.
	O-Ring	Washer	
79.00	3.00	2.87	EKM
79.00	7.00	6.74	EKM
79.40	3.10	2.97	G80
79.50	2.00	1.90	S80
79.50	3.00	2.87	EKM
79.60	5.70	5.53	P80
80.00	2.00	1.90	EKM
80.00	2.50	2.39	EKM
80.00	2.65	2.53	C92
80.00	3.00	2.87	EKM
80.00	3.50	3.37	EKM
80.00	3.55	3.41	C92
80.00	4.00	3.85	EKM
80.00	5.00	4.84	EKM
80.00	5.30	5.13	C92
80.00	6.00	5.78	EKM
80.00	8.00	7.60	EKM
81.92	5.33	5.16	A-339
81.92	5.33	5.16	B-42
81.92	5.33	5.16	R-42
81.92	6.99	6.73	A-415
82.00	3.00	2.87	EKM
82.00	4.00	3.85	EKM
82.00	5.00	4.84	EKM
82.14	3.53	3.39	A-236
82.22	2.62	2.50	A-152
82.27	1.78	1.68	A-042
82.50	3.55	3.41	C92
82.50	5.30	5.13	C92
83.00	3.50	3.37	EKM
84.00	2.00	1.90	EKM
84.00	3.50	3.37	EKM
84.00	4.00	3.85	EKM
84.00	4.00	3.85	V85
84.40	3.10	2.97	G85
84.50	2.00	1.90	S85
84.60	5.70	5.53	P85
85.00	2.00	1.90	EKM
85.00	2.50	2.39	EKM
85.00	2.65	2.53	C92

ID	C/S		NO.
	O-Ring	Washer	
85.00	3.00	2.87	EKM
85.00	3.55	3.41	C92
85.00	4.00	3.85	EKM
85.00	5.00	4.84	EKM
85.00	5.30	5.13	C92
85.09	5.33	5.16	A-340
85.09	5.33	5.16	B-43
85.09	5.33	5.16	R-43
85.09	6.99	6.73	A-416
85.32	3.53	3.39	A-237
86.00	2.00	1.90	EKM
86.00	3.00	2.87	EKM
86.00	4.00	3.85	EKM
87.00	5.00	4.84	EKM
87.50	3.55	3.41	C92
87.50	5.30	5.13	C92
88.00	3.00	2.87	EKM
88.00	4.00	3.85	EKM
88.00	5.00	4.84	EKM
88.00	6.00	5.78	EKM
88.27	5.33	5.16	A-341
88.27	5.33	5.16	B-44
88.27	5.33	5.16	R-44
88.27	6.99	6.73	A-417
88.49	3.53	3.39	A-238
88.57	2.62	2.50	A-153
88.62	1.78	1.68	A-043
89.00	4.50	4.34	EKM
89.40	3.10	2.97	G90
89.50	2.00	1.90	S90
89.60	5.70	5.53	P90
90.00	2.00	1.90	EKM
90.00	2.50	2.39	EKM
90.00	2.65	2.53	C92
90.00	3.00	2.87	EKM
90.00	3.55	3.41	C92
90.00	4.00	3.85	EKM
90.00	5.00	4.84	EKM
90.00	5.30	5.13	C92
90.00	7.00	6.74	EKM

ID	C/S		NO.
	O-Ring	Washer	
91.44	5.33	5.16	A-342
91.44	5.33	5.16	B-45
91.44	5.33	5.16	R-45
91.44	6.99	6.73	A-418
91.67	3.53	3.39	A-239
92.00	3.00	2.87	EKM
92.00	4.00	3.85	EKM
92.00	5.00	4.84	EKM
92.50	3.55	3.41	C92
92.50	5.30	5.13	C92
93.00	3.00	2.87	EKM
93.00	6.50	6.24	EKM
94.00	2.50	2.39	EKM
94.00	3.00	2.87	EKM
94.00	4.00	3.85	EKM
94.40	3.10	2.97	G95
94.50	2.00	1.90	S95
94.60	5.70	5.53	P95
94.62	5.33	5.16	A-343
94.62	5.33	5.16	B-46
94.62	5.33	5.16	R-46
94.62	6.99	6.73	A-419
94.84	3.53	3.39	A-240
94.92	2.62	2.50	A-154
94.97	1.78	1.68	A-044
95.00	2.00	1.90	EKM
95.00	2.50	2.39	EKM
95.00	2.65	2.53	C92
95.00	3.00	2.87	EKM
95.00	3.55	3.41	C92
95.00	4.00	3.85	EKM
95.00	4.50	4.34	EKM
95.00	5.00	4.84	EKM
95.00	5.30	5.13	C92
95.00	6.00	5.78	EKM
96.00	3.00	2.87	EKM
96.00	4.00	3.85	EKM
97.00	5.00	4.84	EKM
97.50	3.55	3.41	C92
97.50	5.30	5.13	C92

ID	C/S		NO.
	O-Ring	Washer	
97.79	5.33	5.16	A-344
97.79	5.33	5.16	B-47
97.79	5.33	5.16	R-47
97.79	6.99	6.73	A-420
98.00	3.00	2.87	EKM
98.00	4.00	3.85	EKM
98.02	3.53	3.39	A-241
99.00	4.00	3.85	V100
99.40	3.10	2.97	G100
99.50	2.00	1.90	S100
99.60	5.70	5.53	P100
ID Over 100mm			
100.00	1.00	0.93	EKM
100.00	1.50	1.42	EKM
100.00	2.00	1.90	EKM
100.00	2.65	2.53	C92
100.00	3.00	2.87	EKM
100.00	3.55	3.41	C92
100.00	4.00	3.85	EKM
100.00	5.00	4.84	EKM
100.00	5.30	5.13	C92
100.00	6.00	5.78	EKM
100.00	7.00	6.74	EKM
100.00	8.00	7.60	EKM
100.96	5.33	5.16	A-345
100.96	5.33	5.16	B-48
100.96	5.33	5.16	R-48
100.96	6.99	6.73	A-421
101.00	3.00	2.87	EKM
101.00	4.50	4.34	EKM
101.19	3.53	3.39	A-242
101.27	2.62	2.50	A-155
101.32	1.78	1.68	A-045
101.50	3.00	2.87	EKM
101.60	5.70	5.53	P102
102.00	3.00	2.87	EKM
102.00	4.00	3.85	EKM
103.00	3.55	3.41	C92
103.00	5.30	5.13	C92

ID	C/S		NO.
	O-Ring	Washer	
103.00	6.00	5.78	EKM
104.00	3.00	2.87	EKM
104.00	4.00	3.85	EKM
104.00	5.00	4.84	EKM
104.00	6.00	5.78	EKM
104.14	5.33	5.16	A-346
104.14	5.33	5.16	B-49
104.14	5.33	5.16	R-49
104.14	6.99	6.73	A-422
104.37	3.53	3.39	A-243
104.40	3.10	2.97	G105
104.50	2.00	1.90	S105
104.50	3.00	2.87	EKM
104.60	5.70	5.53	P105
105.00	2.00	1.90	EKM
105.00	2.50	2.39	EKM
105.00	3.00	2.87	EKM
105.00	3.50	3.37	EKM
105.00	4.00	3.85	EKM
105.00	5.00	4.84	EKM
105.00	6.00	5.78	EKM
106.00	2.00	1.90	EKM
106.00	2.65	2.53	C92
106.00	3.00	2.87	EKM
106.00	3.55	3.41	C92
106.00	5.00	4.84	EKM
106.00	5.30	5.13	C92
106.00	7.00	6.74	EKM
107.00	2.50	2.39	EKM
107.00	5.00	4.84	EKM
107.32	5.33	5.16	A-347
107.32	5.33	5.16	B-50
107.32	5.33	5.16	R-50
107.32	6.99	6.73	A-423
107.54	3.53	3.39	A-244
107.62	2.62	2.50	A-156
107.67	1.78	1.68	A-046
108.00	3.00	2.87	EKM
108.00	4.00	3.85	EKM
108.00	5.00	4.84	EKM


● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available



● If cross section (C/S) is less than 5mm, inside diameter (I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
108.00	6.00	5.78	EKM
108.00	8.00	7.60	EKM
109.00	3.55	3.41	C92
109.00	5.30	5.13	C92
109.00	7.00	6.74	C92
109.40	3.10	2.97	G110
109.50	2.00	1.90	S110
109.50	3.00	2.87	EKM
109.60	5.70	5.53	P110
110.00	2.00	1.90	EKM
110.00	3.00	2.87	EKM
110.00	3.50	3.37	EKM
110.00	4.00	3.85	EKM
110.00	4.50	4.34	EKM
110.00	5.00	4.84	EKM
110.00	6.00	5.78	EKM
110.00	7.00	6.74	EKM
110.00	8.00	7.60	EKM
110.49	5.33	5.16	A-348
110.49	5.33	5.16	B-51
110.49	5.33	5.16	R-51
110.49	6.99	6.73	A-424
110.72	3.53	3.39	A-245
111.50	2.00	1.90	S112
111.60	5.70	5.53	P112
112.00	2.65	2.53	C92
112.00	3.00	2.87	EKM
112.00	3.55	3.41	C92
112.00	4.00	3.85	EKM
112.00	5.00	4.84	EKM
112.00	5.30	5.13	C92
112.00	7.00	6.74	C92
112.00	8.00	7.60	EKM
113.67	5.33	5.16	A-349
113.67	5.33	5.16	B-52
113.67	5.33	5.16	R-52
113.67	6.99	6.73	A-425
113.67	6.99	6.73	R-53
113.89	3.53	3.39	A-246
113.97	2.62	2.50	A-157

ID	C/S		NO.
	O-Ring	Washer	
114.00	3.00	2.87	EKM
114.00	4.00	3.85	EKM
114.00	6.00	5.78	EKM
114.00	7.00	6.74	EKM
114.00	8.00	7.60	EKM
114.02	1.78	1.68	A-047
114.40	3.10	2.97	G115
114.50	2.00	1.90	S115
114.60	5.70	5.53	P115
115.00	2.00	1.90	EKM
115.00	2.50	2.39	EKM
115.00	3.00	2.87	EKM
115.00	3.55	3.41	C92
115.00	4.00	3.85	EKM
115.00	4.50	4.34	EKM
115.00	5.00	4.84	EKM
115.00	5.30	5.13	C92
115.00	6.00	5.78	EKM
115.00	7.00	6.74	C92
116.00	3.00	2.87	EKM
116.00	4.00	3.85	EKM
116.84	5.33	5.16	A-350
116.84	6.99	6.73	A-426
116.84	6.99	6.73	B-53
116.84	6.99	6.73	R-54
117.00	4.00	3.85	EKM
117.00	7.00	6.74	EKM
117.07	3.53	3.39	A-247
118.00	2.00	1.90	EKM
118.00	2.65	2.53	C92
118.00	3.00	2.87	EKM
118.00	3.55	3.41	C92
118.00	4.00	3.85	EKM
118.00	4.50	4.34	EKM
118.00	5.00	4.84	EKM
118.00	5.30	5.13	C92
118.00	6.00	5.78	EKM
118.00	7.00	6.74	C92
119.00	3.00	2.87	EKM
119.00	4.00	3.85	V120

ID	C/S		NO.
	O-Ring	Washer	
119.40	3.10	2.97	G120
119.50	2.00	1.90	S120
119.60	5.70	5.53	P120
120.00	2.00	1.90	EKM
120.00	2.50	2.39	EKM
120.00	3.00	2.87	EKM
120.00	3.50	3.37	EKM
120.00	4.00	3.85	EKM
120.00	4.50	4.34	EKM
120.00	5.00	4.84	EKM
120.00	6.00	5.78	EKM
120.02	5.33	5.16	A-351
120.02	6.99	6.73	A-427
120.02	6.99	6.73	B-54
120.02	6.99	6.73	R-55
120.24	3.53	3.39	A-248
120.32	2.62	2.50	A-158
120.37	1.78	1.68	A-048
121.00	5.00	4.84	EKM
122.00	3.00	2.87	EKM
122.00	3.55	3.41	C92
122.00	4.00	3.85	EKM
122.00	4.50	4.34	EKM
122.00	5.00	4.84	EKM
122.00	5.30	5.13	C92
122.00	6.00	5.78	EKM
122.00	7.00	6.74	C92
122.00	8.00	7.60	EKM
123.00	6.00	5.78	EKM
123.19	5.33	5.16	A-352
123.19	6.99	6.73	A-428
123.19	6.99	6.73	B-55
123.19	6.99	6.73	R-56
123.42	3.53	3.39	A-249
124.00	3.00	2.87	EKM
124.00	4.00	3.85	EKM
124.40	3.10	2.97	G125
124.50	2.00	1.90	S125
124.60	5.70	5.53	P125
125.00	2.00	1.90	EKM

ID	C/S		NO.
	O-Ring	Washer	
125.00	2.50	2.39	EKM
125.00	2.65	2.53	C92
125.00	3.00	2.87	EKM
125.00	3.50	3.37	EKM
125.00	3.55	3.41	C92
125.00	4.00	3.85	EKM
125.00	5.00	4.84	EKM
125.00	5.30	5.13	C92
125.00	6.00	5.78	EKM
125.00	7.00	6.74	C92
126.00	4.00	3.85	EKM
126.00	4.50	4.34	EKM
126.37	5.33	5.16	A-353
126.37	6.99	6.73	A-429
126.37	6.99	6.73	B-56
126.37	6.99	6.73	R-57
126.59	3.53	3.39	A-250
126.67	2.62	2.50	A-159
126.72	1.78	1.68	A-049
127.00	4.00	3.85	EKM
128.00	2.00	1.90	EKM
128.00	2.50	2.39	EKM
128.00	3.00	2.87	EKM
128.00	3.55	3.41	C92
128.00	4.00	3.85	EKM
128.00	5.30	5.13	C92
128.00	6.00	5.78	EKM
128.00	7.00	6.74	C92
128.00	9.00	8.55	EKM
129.00	4.00	3.85	EKM
129.40	3.10	2.97	G130
129.50	2.00	1.90	S130
129.54	5.33	5.16	A-354
129.54	6.99	6.73	A-430
129.54	6.99	6.73	B-57
129.54	6.99	6.73	R-58
129.60	5.70	5.53	P130
129.77	3.53	3.39	A-251
130.00	2.00	1.90	EKM
130.00	2.50	2.39	EKM

ID	C/S		NO.
	O-Ring	Washer	
130.00	3.00	2.87	EKM
130.00	4.00	3.85	EKM
130.00	4.50	4.34	EKM
130.00	5.00	4.84	EKM
130.00	6.00	5.78	EKM
130.00	8.00	7.60	EKM
131.50	2.00	1.90	S132
131.60	5.70	5.53	P132
132.00	2.65	2.53	C92
132.00	3.00	2.87	EKM
132.00	3.55	3.41	C92
132.00	4.00	3.85	EKM
132.00	5.00	4.84	EKM
132.00	5.30	5.13	C92
132.00	7.00	6.74	C92
132.00	8.00	7.60	EKM
132.72	5.33	5.16	A-355
132.72	6.99	6.73	A-431
132.72	6.99	6.73	B-58
132.72	6.99	6.73	R-59
132.94	3.53	3.39	A-252
133.00	3.50	3.37	EKM
133.00	4.00	3.85	EKM
133.02	2.62	2.50	A-160
133.07	1.78	1.68	A-050
134.00	3.00	2.87	EKM
134.00	4.00	3.85	EKM
134.40	3.10	2.97	G135
134.50	2.00	1.90	S135
134.60	5.70	5.53	P135
135.00	2.50	2.39	EKM
135.00	3.00	2.87	EKM
135.00	3.50	3.37	EKM
135.00	4.00	3.85	EKM
135.00	5.00	4.84	EKM
135.00	6.00	5.78	EKM
135.89	5.33	5.16	A-356
135.89	6.99	6.73	A-432
135.89	6.99	6.73	B-59
135.89	6.99	6.73	R-60


ID	C/S		NO.
	O-Ring	Washer	
136.00	3.50	3.37	EKM
136.00	3.55	3.41	C92
136.00	4.00	3.85	EKM
136.00	5.00	4.84	EKM
136.00	5.30	5.13	C92
136.00	7.00	6.74	C92
136.12	3.53	3.39	A-253
137.00	4.00	3.85	EKM
138.00	3.00	2.87	EKM
138.00	5.00	4.84	EKM
138.00	6.00	5.78	EKM
139.00	7.00	6.74	EKM
139.07	5.33	5.16	A-357
139.07	6.99	6.73	A-433
139.07	6.99	6.73	B-60
139.07	6.99	6.73	R-61
139.29	3.53	3.39	A-254
139.37	2.62	2.50	A-161
139.40	3.10	2.97	G140
139.50	2.00	1.90	S140
139.50	3.00	2.87	EKM
139.60	5.70	5.53	P140
140.00	2.00	1.90	EKM
140.00	2.50	2.39	EKM
140.00	2.65	2.53	C92
140.00	3.00	2.87	EKM
140.00	3.55	3.41	C92
140.00	4.00	3.85	EKM
140.00	5.00	4.84	EKM
140.00	5.30	5.13	C92
140.00	6.00	5.78	EKM
140.00	7.00	6.74	C92
140.00	8.00	7.60	EKM
142.00	3.00	2.87	EKM
142.00	4.00	3.85	EKM
142.00	6.00	5.78	EKM
142.24	5.33	5.16	A-358
142.24	6.99	6.73	A-434
142.24	6.99	6.73	B-61
142.24	6.99	6.73	R-62

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
142.47	3.53	3.39	A-255
143.00	2.00	1.90	EKM
144.00	3.00	2.87	EKM
144.00	4.00	3.85	EKM
144.00	5.00	4.84	EKM
144.40	3.10	2.97	G145
144.50	2.00	1.90	S145
144.60	5.70	5.53	P145
145.00	2.50	2.39	EKM
145.00	3.50	3.37	EKM
145.00	3.55	3.41	C92
145.00	4.00	3.85	EKM
145.00	5.00	4.84	EKM
145.00	5.30	5.13	C92
145.00	7.00	6.74	C92
145.00	8.00	7.60	EKM
145.42	5.33	5.16	A-359
145.42	6.99	6.73	A-435
145.42	6.99	6.73	B-62
145.42	6.99	6.73	R-63
145.64	3.53	3.39	A-256
145.72	2.62	2.50	A-162
146.00	3.00	2.87	EKM
146.00	4.00	3.85	EKM
148.00	6.00	5.78	EKM
148.50	4.00	3.85	V150
148.59	5.33	5.16	A-360
148.59	6.99	6.73	A-436
148.59	6.99	6.73	B-63
148.59	6.99	6.73	R-64
148.82	3.53	3.39	A-257
149.00	3.00	2.87	EKM
149.30	5.70	5.53	G150
149.50	2.00	1.90	S150
149.50	8.40	7.98	P150A
149.60	5.70	5.53	P150
ID Over 150mm			
150.00	2.00	1.90	EKM
150.00	2.50	2.39	EKM

ID	C/S		NO.
	O-Ring	Washer	
150.00	2.65	2.53	C92
150.00	3.00	2.87	EKM
150.00	3.55	3.41	C92
150.00	4.00	3.85	EKM
150.00	4.50	4.34	EKM
150.00	5.00	4.84	EKM
150.00	5.30	5.13	C92
150.00	6.00	5.78	EKM
150.00	7.00	6.74	C92
150.00	8.00	7.60	EKM
151.77	5.33	5.16	A-361
151.77	6.99	6.73	A-437
151.77	6.99	6.73	B-64
151.77	6.99	6.73	R-65
151.99	3.53	3.39	A-258
152.00	5.00	4.84	EKM
152.00	7.00	6.74	EKM
152.07	2.62	2.50	A-163
153.00	3.00	2.87	EKM
153.00	6.00	5.78	EKM
154.00	3.00	2.87	EKM
154.30	5.70	5.53	G155
154.50	8.40	7.98	P155
155.00	3.00	2.87	EKM
155.00	3.55	3.41	C92
155.00	4.00	3.85	EKM
155.00	5.00	4.84	EKM
155.00	5.30	5.13	C92
155.00	7.00	6.74	C92
156.00	2.00	1.90	EKM
156.00	4.00	3.85	EKM
158.00	5.00	4.84	EKM
158.00	6.00	5.78	EKM
158.12	5.33	5.16	A-362
158.12	6.99	6.73	A-438
158.12	6.99	6.73	B-65
158.12	6.99	6.73	R-66
158.34	3.53	3.39	A-259
158.42	2.62	2.50	A-164
159.00	4.00	3.85	EKM

ID	C/S		NO.
	O-Ring	Washer	
159.30	5.70	5.53	G160
159.50	8.40	7.98	P160
160.00	2.00	1.90	EKM
160.00	2.50	2.39	EKM
160.00	2.65	2.53	C92
160.00	3.00	2.87	EKM
160.00	3.55	3.41	C92
160.00	4.00	3.85	EKM
160.00	4.50	4.34	EKM
160.00	5.00	4.84	EKM
160.00	5.30	5.13	C92
160.00	5.30	5.13	C92
160.00	6.00	5.78	EKM
160.00	7.00	6.74	C92
160.00	8.00	7.60	EKM
160.00	8.00	7.60	EKM
164.00	3.00	2.87	EKM
164.00	4.00	3.85	EKM
164.30	5.70	5.53	G165
164.46	5.33	5.16	A-363
164.47	6.99	6.73	A-439
164.47	6.99	6.73	B-66
164.47	6.99	6.73	R-67
164.50	8.40	7.98	P165
164.69	3.53	3.39	A-260
164.77	2.62	2.50	A-165
165.00	2.00	1.90	EKM
165.00	3.50	3.37	EKM
165.00	3.55	3.41	C92
165.00	4.00	3.85	EKM
165.00	5.00	4.84	EKM
165.00	5.30	5.13	C92
165.00	7.00	6.74	C92
166.00	6.00	5.78	EKM
167.00	3.00	2.87	EKM
168.00	4.00	3.85	EKM
169.30	5.70	5.53	G170
169.50	8.40	7.98	P170
170.00	2.50	2.39	EKM
170.00	2.65	2.53	C92
170.00	3.00	2.87	EKM
170.00	3.50	3.37	EKM

ID	C/S		NO.
	O-Ring	Washer	
170.00	3.55	3.41	C92
170.00	4.00	3.85	EKM
170.00	5.00	4.84	EKM
170.00	5.30	5.13	C92
170.00	6.00	5.78	EKM
170.00	7.00	6.74	C92
170.00	8.00	7.60	EKM
170.82	5.33	5.16	A-364
170.82	6.99	6.73	A-440
170.82	6.99	6.73	B-67
170.82	6.99	6.73	R-68
171.04	3.53	3.39	A-261
171.12	2.62	2.50	A-166
172.00	4.00	3.85	EKM
172.00	6.00	5.78	EKM
172.00	7.00	6.74	EKM
173.00	4.00	3.85	V175
174.00	3.00	2.87	EKM
174.30	5.70	5.53	G175
174.50	8.40	7.98	P175
175.00	3.55	3.41	C92
175.00	4.00	3.85	EKM
175.00	5.00	4.84	EKM
175.00	5.30	5.13	C92
175.00	6.00	5.78	EKM
175.00	7.00	6.74	C92
177.00	3.50	3.37	EKM
177.00	4.00	3.85	EKM
177.17	5.33	5.16	A-365
177.17	6.99	6.73	A-441
177.17	6.99	6.73	B-68
177.17	6.99	6.73	R-69
177.39	3.53	3.39	A-262
177.47	2.62	2.50	A-167
179.00	3.00	2.87	EKM
179.30	5.70	5.53	G180
179.50	8.40	7.98	P180
180.00	1.50	1.42	EKM
180.00	2.65	2.53	C92
180.00	3.00	2.87	EKM

ID	C/S		NO.
	O-Ring	Washer	
180.00	3.50	3.37	EKM
180.00	3.55	3.41	C92
180.00	4.00	3.85	EKM
180.00	5.00	4.84	EKM
180.00	5.30	5.13	C92
180.00	6.00	5.78	EKM
180.00	7.00	6.74	C92
180.00	8.00	7.60	EKM
182.00	3.00	2.87	EKM
182.00	6.00	5.78	EKM
183.52	5.33	5.16	A-366
183.52	6.99	6.73	A-442
183.52	6.99	6.73	B-69
183.52	6.99	6.73	R-70
183.74	3.53	3.39	A-263
183.82	2.62	2.50	A-168
184.00	3.00	2.87	EKM
184.00	8.00	7.60	EKM
184.30	5.70	5.53	G185
184.50	8.40	7.98	P185
185.00	3.00	2.87	EKM
185.00	3.55	3.41	C92
185.00	4.00	3.85	EKM
185.00	4.50	4.34	EKM
185.00	5.00	4.84	EKM
185.00	5.30	5.13	C92
185.00	6.00	5.78	EKM
185.00	7.00	6.74	C92
186.00	3.50	3.37	EKM
186.00	7.00	6.74	EKM
188.00	2.00	1.90	EKM
188.00	3.00	2.87	EKM
188.00	4.00	3.85	EKM
188.00	6.00	5.78	EKM
189.30	5.70	5.53	G190
189.50	8.40	7.98	P190
189.87	5.33	5.16	A-367
189.87	6.99	6.73	A-443
189.87	6.99	6.73	B-70
189.87	6.99	6.73	R-71


ID	C/S		NO.
	O-Ring	Washer	
190.00	3.00	2.87	EKM
190.00	3.50	3.37	EKM
190.00	3.55	3.41	C92
190.00	4.00	3.85	EKM
190.00	5.00	4.84	EKM
190.00	5.30	5.13	C92
190.00	6.00	5.78	EKM
190.00	7.00	6.74	C92
190.00	7.00	6.74	EKM
190.00	8.00	7.60	EKM
190.10	3.53	3.39	A-264
190.17	2.62	2.50	A-169
192.00	2.00	1.90	EKM
192.00	3.00	2.87	EKM
192.00	4.00	3.85	EKM
193.00	6.00	5.78	EKM
194.00	2.00	1.90	EKM
194.00	3.00	2.87	EKM
194.30	5.70	5.53	G195
194.50	8.40	7.98	P195
195.00	2.50	2.39	EKM
195.00	3.00	2.87	EKM
195.00	3.50	3.37	EKM
195.00	3.55	3.41	C92
195.00	4.00	3.85	EKM
195.00	5.00	4.84	EKM
195.00	5.30	5.13	C92
195.00	6.00	5.78	EKM
195.00	7.00	6.74	C92
196.22	5.33	5.16	A-368
196.22	6.99	6.73	A-444
196.22	6.99	6.73	B-71
196.22	6.99	6.73	R-72
196.44	3.53	3.39	A-265
196.52	2.62	2.50	A-170
198.00	4.00	3.85	EKM
199.30	5.70	5.53	G200
199.50	8.40	7.98	P200
ID Over 200mm			

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring



ID	C/S		NO.
	O-Ring	Washer	
200.00	2.00	1.90	EKM
200.00	3.00	2.87	EKM
200.00	3.55	3.41	C92
200.00	3.55	3.41	EKM
200.00	4.00	3.85	EKM
200.00	5.00	4.84	EKM
200.00	5.30	5.13	C92
200.00	6.00	5.78	EKM
200.00	7.00	6.74	C92
202.00	3.50	3.37	EKM
202.00	5.50	5.33	EKM
202.57	5.33	5.16	A-369
202.57	6.99	6.73	A-445
202.57	6.99	6.73	B-72
202.57	6.99	6.73	R-73
202.79	3.53	3.39	A-266
202.87	2.62	2.50	A-171
203.00	3.00	2.87	EKM
204.00	4.00	3.85	EKM
204.00	6.00	5.78	EKM
204.50	8.40	7.98	P205
205.00	2.00	1.90	EKM
205.00	3.00	2.87	EKM
205.00	5.00	4.84	EKM
205.00	6.00	5.78	EKM
206.00	7.00	6.74	C92
208.00	6.00	5.78	EKM
208.00	8.00	7.60	EKM
208.50	8.40	7.98	P209
208.92	5.33	5.16	A-370
209.14	3.53	3.39	A-267
209.22	2.62	2.50	A-172
209.30	5.70	5.53	G210
209.50	8.40	7.98	P210
210.00	3.00	2.87	EKM
210.00	3.50	3.37	EKM
210.00	4.00	3.85	EKM
210.00	5.00	4.84	EKM
210.00	6.00	5.78	EKM
210.00	8.00	7.60	EKM

ID	C/S		NO.
	O-Ring	Washer	
212.00	4.00	3.85	EKM
212.00	5.30	5.13	C92
212.00	6.00	5.78	EKM
212.00	7.00	6.74	C92
214.50	8.40	7.98	P215
215.00	3.00	2.87	EKM
215.00	5.00	4.84	EKM
215.00	6.00	5.78	EKM
215.00	7.00	6.74	EKM
215.27	5.33	5.16	A-371
215.27	6.99	6.73	A-446
215.27	6.99	6.73	B-73
215.27	6.99	6.73	R-74
215.49	3.53	3.39	A-268
215.57	2.62	2.50	A-173
216.00	4.00	3.85	EKM
217.00	3.00	2.87	EKM
217.00	5.00	4.84	EKM
218.00	6.00	5.78	EKM
218.00	7.00	6.74	C92
219.30	5.70	5.53	G220
219.50	8.40	7.98	P220
220.00	3.00	2.87	EKM
220.00	4.00	3.85	EKM
220.00	5.00	4.84	EKM
220.00	6.00	5.78	EKM
221.62	5.33	5.16	A-372
221.84	3.53	3.39	A-269
221.92	2.62	2.50	A-174
222.00	4.00	3.85	EKM
222.50	6.00	5.78	V225
224.00	5.30	5.13	C92
224.00	7.00	6.74	C92
224.50	8.40	7.98	P225
225.00	3.00	2.87	EKM
225.00	4.00	3.85	EKM
225.00	5.00	4.84	EKM
226.00	8.00	7.60	EKM
227.97	5.33	5.16	A-373
227.97	6.99	6.73	A-447

ID	C/S		NO.
	O-Ring	Washer	
227.97	6.99	6.73	B-74
227.97	6.99	6.73	R-75
228.00	4.00	3.85	EKM
228.19	3.53	3.39	A-270
228.27	2.62	2.50	A-175
229.30	5.70	5.53	G230
229.50	8.40	7.98	P230
230.00	3.00	2.87	EKM
230.00	4.00	3.85	EKM
230.00	5.00	4.84	EKM
230.00	6.00	5.78	EKM
230.00	7.00	6.74	C92
230.00	8.00	7.60	EKM
233.00	3.00	2.87	EKM
234.32	5.33	5.16	A-374
234.50	8.40	7.98	P235
234.54	3.53	3.39	A-271
234.62	2.62	2.50	A-176
235.00	3.00	2.87	EKM
235.00	4.00	3.85	EKM
235.00	5.00	4.84	EKM
235.00	7.00	6.74	EKM
236.00	5.30	5.13	C92
236.00	7.00	6.74	C92
238.00	5.00	4.84	EKM
239.30	5.70	5.53	G240
239.50	8.40	7.98	P240
240.00	3.00	2.87	EKM
240.00	4.00	3.85	EKM
240.00	5.00	4.84	EKM
240.00	6.00	5.78	EKM
240.00	8.00	7.60	EKM
240.67	5.33	5.16	A-375
240.67	6.99	6.73	A-448
240.67	6.99	6.73	B-75
240.67	6.99	6.73	R-76
240.89	3.53	3.39	A-272
240.97	2.62	2.50	A-177
242.00	6.00	5.78	EKM
243.00	7.00	6.74	C92


ID	C/S		NO.
	O-Ring	Washer	
243.00	8.50	8.08	EKM
244.00	7.00	6.74	EKM
244.50	8.40	7.98	P245
245.00	3.00	2.87	EKM
245.00	5.00	4.84	EKM
246.00	4.00	3.85	EKM
247.00	7.00	6.74	EKM
247.02	5.33	5.16	A-376
247.24	3.53	3.39	A-273
247.32	2.62	2.50	A-178
248.00	5.00	4.84	EKM
249.30	5.70	5.53	G250
249.50	8.40	7.98	P250
ID Over 250mm			
250.00	3.00	2.87	EKM
250.00	4.00	3.85	EKM
250.00	5.00	4.84	EKM
250.00	5.30	5.13	C92
250.00	6.00	5.78	EKM
250.00	7.00	6.74	C92
250.00	7.00	6.74	EKM
250.00	8.00	7.60	EKM
253.37	5.33	5.16	A-377
253.37	6.99	6.73	A-449
253.37	6.99	6.73	B-76
253.37	6.99	6.73	R-77
253.59	3.53	3.39	A-274
254.50	8.40	7.98	P255
255.00	4.00	3.85	EKM
255.00	5.00	4.84	EKM
258.00	7.00	6.74	C92
259.30	5.70	5.53	G260
259.50	8.40	7.98	P260
260.00	2.50	2.39	EKM
260.00	3.00	2.87	EKM
260.00	4.00	3.85	EKM
260.00	5.00	4.84	EKM
260.00	6.00	5.78	EKM
260.00	7.00	6.74	EKM

ID	C/S		NO.
	O-Ring	Washer	
260.00	8.00	7.60	EKM
262.00	6.00	5.78	EKM
264.50	8.40	7.98	P265
265.00	3.00	2.87	EKM
265.00	4.00	3.85	EKM
265.00	5.00	4.84	EKM
265.00	5.30	5.13	C92
265.00	6.00	5.78	EKM
265.00	7.00	6.74	C92
265.00	8.00	7.60	EKM
266.07	5.33	5.16	A-378
266.07	6.99	6.73	A-450
266.07	6.99	6.73	B-77
266.07	6.99	6.73	R-78
266.29	3.53	3.39	A-275
269.30	5.70	5.53	G270
269.50	8.40	7.98	P270
270.00	3.00	2.87	EKM
270.00	4.00	3.85	EKM
270.00	5.00	4.84	EKM
270.00	6.00	5.78	EKM
272.00	6.00	5.78	V275
272.00	7.00	6.74	C92
274.00	3.00	2.87	EKM
274.50	8.40	7.98	P275
275.00	4.00	3.85	EKM
275.00	5.00	4.84	EKM
278.77	5.33	5.16	A-379
278.77	6.99	6.73	A-451
278.77	6.99	6.73	B-78
278.77	6.99	6.73	R-79
278.99	3.53	3.39	A-276
279.30	5.70	5.53	G280
279.50	8.40	7.98	P280
280.00	3.00	2.87	EKM
280.00	4.00	3.85	EKM
280.00	5.00	4.84	EKM
280.00	5.30	5.13	C92
280.00	6.00	5.78	EKM
280.00	7.00	6.74	C92


ID	C/S		NO.
	O-Ring	Washer	
280.00	8.00	7.60	EKM
282.00	4.00	3.85	EKM
284.00	6.00	5.78	EKM
284.50	8.40	7.98	P285
285.00	3.00	2.87	EKM
285.00	4.00	3.85	EKM
289.30	5.70	5.53	G290
289.50	8.40	7.98	P290
290.00	3.00	2.87	EKM
290.00	5.00	4.84	EKM
290.00	6.00	5.78	EKM
290.00	7.00	6.74	C92
290.00	8.00	7.60	EKM
291.47	5.33	5.16	A-380
291.47	6.99	6.73	A-452
291.47	6.99	6.73	B-79
291.47	6.99	6.73	R-80
291.69	3.53	3.39	A-277
292.00	4.00	3.85	EKM
294.50	8.40	7.98	P295
295.00	6.00	5.78	EKM
297.00	4.00	3.85	EKM
299.30	5.70	5.53	G300
299.50	8.40	7.98	P300
ID Over 300mm			
300.00	3.00	2.87	EKM
300.00	5.00	4.84	EKM
300.00	5.30	5.13	C92
300.00	6.00	5.78	EKM
300.00	7.00	6.74	C92
304.17	5.33	5.16	A-381
304.17	6.99	6.73	A-453
304.17	6.99	6.73	B-80
304.17	6.99	6.73	R-81
304.39	3.53	3.39	A-278
305.00	4.00	3.85	EKM
305.00	5.00	4.84	EKM
307.00	7.00	6.74	C92
310.00	3.00	2.87	EKM

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available

● If cross section (C/S) is less than 5mm, inside diameter (I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.



O-Ring




ID	C/S		NO.
	O-Ring	Washer	
310.00	4.00	3.85	EKM
310.00	5.00	4.84	EKM
314.00	8.00	7.60	EKM
314.50	8.40	7.98	P315
315.00	4.00	3.85	EKM
315.00	5.00	4.84	EKM
315.00	5.30	5.13	C92
315.00	6.00	5.78	EKM
315.00	7.00	6.74	C92
316.87	6.99	6.73	A-454
316.87	6.99	6.73	B-81
316.87	6.99	6.73	R-82
319.50	8.40	7.98	P320
320.00	2.50	2.39	EKM
320.00	3.00	2.87	EKM
320.00	5.00	4.84	EKM
320.00	6.00	5.78	EKM
320.00	7.00	6.74	EKM
320.00	8.00	7.60	EKM
321.50	6.00	5.78	V325
325.00	5.00	4.84	EKM
325.00	6.00	5.78	EKM
325.00	7.00	6.74	C92
329.57	5.33	5.16	A-382
329.57	6.99	6.73	A-455
329.57	6.99	6.73	B-82
329.57	6.99	6.73	R-83
329.79	3.53	3.39	A-279
330.00	4.00	3.85	EKM
330.00	5.00	4.84	EKM
330.00	6.00	5.78	EKM
330.00	8.00	7.60	EKM
331.00	3.00	2.87	EKM
334.50	8.40	7.98	P335
335.00	5.30	5.13	C92
335.00	6.00	5.78	EKM
335.00	7.00	6.74	C92
339.50	8.40	7.98	P340
340.00	3.50	3.37	EKM
340.00	4.00	3.85	EKM

ID	C/S		NO.
	O-Ring	Washer	
340.00	5.00	4.84	EKM
340.00	6.00	5.78	EKM
342.00	8.00	7.60	EKM
342.27	6.99	6.73	A-456
342.27	6.99	6.73	B-83
342.27	6.99	6.73	R-84
345.00	5.00	4.84	EKM
345.00	7.00	6.74	C92
347.00	9.00	8.55	EKM
350.00	5.00	4.84	EKM
354.50	8.40	7.98	P355
354.97	5.33	5.16	A-383
354.97	6.99	6.73	A-457
354.97	6.99	6.73	B-84
354.99	6.99	6.73	R-85
355.00	4.00	3.85	EKM
355.00	5.00	4.84	EKM
355.00	5.30	5.13	C92
355.00	6.00	5.78	EKM
355.00	7.00	6.74	C92
355.19	3.53	3.39	A-280
359.50	8.40	7.98	P360
360.00	4.00	3.85	EKM
360.00	8.00	7.60	EKM
365.00	7.00	6.74	C92
367.00	3.50	3.37	EKM
367.00	5.00	4.84	EKM
367.67	6.99	6.73	A-458
367.67	6.99	6.73	B-85
367.67	6.99	6.73	R-86
368.00	6.00	5.78	EKM
370.00	4.00	3.85	EKM
370.00	5.00	4.84	EKM
371.00	8.50	8.08	EKM
374.00	8.00	7.60	EKM
374.50	8.40	7.98	P375
375.00	5.00	4.84	EKM
375.00	5.30	5.13	C92
375.00	7.00	6.74	C92
376.00	6.00	5.78	EKM

ID	C/S		NO.
	O-Ring	Washer	
376.00	6.00	5.78	V380
380.00	3.00	2.87	EKM
380.00	4.00	3.85	EKM
380.00	8.00	7.60	EKM
380.37	5.33	5.16	A-384
380.37	6.99	6.73	A-459
380.37	6.99	6.73	B-86
380.37	6.99	6.73	R-87
380.59	3.53	3.39	A-281
384.50	8.40	7.98	P385
385.00	5.00	4.84	EKM
386.00	6.00	5.78	EKM
387.00	7.00	6.74	C92
390.00	4.00	3.85	EKM
390.00	9.00	8.55	EKM
393.07	6.99	6.73	A-460
393.07	6.99	6.73	B-87
393.07	6.99	6.73	R-88
395.00	5.00	4.84	EKM
399.50	8.40	7.98	P400
ID Over 400mm			
400.00	4.00	3.85	EKM
400.00	5.00	4.84	EKM
400.00	5.30	5.13	C92
400.00	7.00	6.74	C92
400.00	8.00	7.60	EKM
405.26	3.53	3.39	A-282
405.26	5.33	5.16	A-385
405.26	6.99	6.73	A-461
410.00	4.00	3.85	EKM
410.00	8.00	7.60	EKM
412.00	7.00	6.74	C92
412.00	8.00	7.60	EKM
415.00	5.00	4.84	EKM
417.96	6.99	6.73	A-462
417.96	6.99	6.73	B-88
420.00	4.00	3.85	EKM
420.00	5.00	4.84	EKM
425.00	4.00	3.85	EKM

● X-Ring: ID ≥ 2.90mm, C/S ≥ 1.78mm is available



A= AS568, B= BS1516, C=C92

V.S.P.G = JIS EKM=EKStandard, R = France

ID	C/S		NO.
	O-Ring	Washer	
425.00	7.00	6.74	C92
425.00	8.00	7.60	EKM
425.50	6.00	5.78	V430
429.00	6.00	5.78	EKM
430.66	3.53	3.39	A-283
430.66	5.33	5.16	A-386
430.66	6.99	6.73	A-463
437.00	7.00	6.74	C92
440.00	4.00	3.85	EKM
443.36	6.99	6.73	A-464
444.00	8.00	7.60	EKM
448.00	6.00	5.78	EKM
450.00	5.00	4.84	EKM
450.00	7.00	6.74	C92
456.06	3.53	3.39	A-284
456.06	5.33	5.16	A-387
456.06	6.99	6.73	A-465
460.00	4.00	3.85	EKM
460.00	5.00	4.84	EKM
460.00	8.00	7.60	EKM
462.00	7.00	6.74	C92
468.76	6.99	6.73	A-466
470.00	4.00	3.85	EKM
470.00	6.00	5.78	EKM
475.00	5.00	4.84	EKM

ID	C/S		NO.
	O-Ring	Washer	
475.00	7.00	6.74	C92
475.60	10.00	9.50	V480
480.00	6.00	5.78	EKM
481.46	5.33	5.16	A-388
481.46	6.99	6.73	A-467
487.00	7.00	6.74	C92
490.00	5.00	4.84	EKM
490.00	8.00	7.60	EKM
492.00	4.00	3.85	EKM
494.16	6.99	6.73	A-468
ID Over 500mm			
500.00	7.00	6.74	C92
506.86	5.33	5.16	A-389
506.86	6.99	6.73	A-469
515.00	7.00	6.74	C92
524.50	10.00	9.50	V530
530.00	7.00	6.74	C92
532.26	5.33	5.16	A-390
532.26	6.99	6.73	A-470
545.00	7.00	6.74	C92
557.66	5.33	5.16	A-391
557.66	6.99	6.73	A-471
560.00	7.00	6.74	C92
579.00	10.00	9.50	V585

ID	C/S		NO.
	O-Ring	Washer	
580.00	7.00	6.74	C92
582.68	5.33	5.16	A-392
582.68	6.99	6.73	A-472
ID Over 600mm			
600.00	7.00	6.74	C92
608.08	5.33	5.16	A-393
608.08	6.99	6.73	A-473
615.00	7.00	6.74	C92
630.00	7.00	6.74	C92
633.48	5.33	5.16	A-394
633.48	6.99	6.73	A-474
633.50	10.00	9.50	V640
650.00	7.00	6.74	C92
658.88	5.33	5.16	A-395
658.88	6.99	6.73	A-475
670.00	7.00	6.74	C92
683.00	10.00	9.50	V690
ID Over 700mm			
732.50	10.00	9.50	V740
782.00	10.00	9.50	V790
836.50	10.00	9.50	V845
940.50	10.00	9.50	V950
1044.00	10.00	9.50	V1055

Remarks

1. NBR70/VMQ70/FKM75: With Stock
2. Other rubber Material Hardness. (see page8 Material/page5 Hardness)
3. PU. PTFE. Parts Available

● If cross section(C/S) is less than 5mm, inside diameter(I.D.) should be more than 20mm, and if C/S is more than 5mm, then I.D. should be more than 40mm.

